



THEA

Domus Line design

Surface aluminium LED profile

Materials:

aluminium, polycarbonate, thermoplastic polymers

Finishes:

aluminium, black matt, dark stainless

Light source:

SHE LED module (180 LED/m)

Wiring:



2000mm

Application type:



under cabinet

Installation:



surface



Colour appearance natural white
Colour temperature 4000 K
Luminous efficiency 85 lm/W
CRI Ra ≥ 80




Colour appearance warm white
Colour temperature 3000 K
Luminous efficiency 85 lm/W
CRI Ra ≥ 80



Colour appearance super warm white
Colour temperature 2700 K
Luminous efficiency 85 lm/W
CRI Ra ≥ 80

* values referring to THEA SHE 1200mm



THEA SHE
without switch



Code	Length	Watt & Volt
13230_ _ _ **/1	450mm	6,2W @ 24Vdc
13231_ _ _ **/1	600mm	8,2W @ 24Vdc
13232_ _ _ **/1	800mm	11W @ 24Vdc
13233_ _ _ **/1	900mm	12,5W @ 24Vdc
13234_ _ _ **/1	1000mm	13,9W @ 24Vdc
13235_ _ _ **/1	1200mm	16,8W @ 24Vdc


CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



Code	Finish*
05	aluminium
32	black matt
50	dark stainless

Code	Light colour**
N	natural white
B	warm white
B1	super warm white

This profile integrates a stripled with OSRAM Opto Semiconductors diodes.



THEA SHE TD
with touch dimmable switch



Code	Length	Watt & Volt
13230_ _ _ **	450mm	6,2W @ 24Vdc
13231_ _ _ **	600mm	8,2W @ 24Vdc
13232_ _ _ **	800mm	11W @ 24Vdc
13233_ _ _ **	900mm	12,5W @ 24Vdc
13234_ _ _ **	1000mm	13,9W @ 24Vdc
13235_ _ _ **	1200mm	16,8W @ 24Vdc

CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



This profile integrates a stripled with OSRAM Opto Semiconductors diodes.



Code	Finish*
05	aluminium
32	black matt
50	dark stainless


Code	Light colour**
N	natural white
B	warm white

THEA profile alone with relative accessories (screen and heads) for customisation also available. For details consult the **Flexyled collection catalogue** available also on www.domusline.com



THEA TD
with touch dimmer switch

THEA TD has an electronic touch dimmer switch, which adjusts the brightness and turns the luminaire on and off "at a touch".



THEA is easily installed on surface with steel clips hidden on the back of the profile.



For LED converters and accessories see page 76 or consult the **Domus Extra catalogue** also available on www.domusline.com.



THEA is a profile with asymmetric light-beam projection designed for under-cabinet surface installation against the wall. Available in the SHE version (180 LED/m), **THEA** is provided with hidden fixing clips and power cord with back exit.

FINISHES



ALUMINIUM (code 05)



BLACK MATT (code 32)



DARK STAINLESS (code 50)

¹ For UL-certified model codes, see the **American standard LED collection catalogue**, also available at www.domusline.com.

